


| TECHNICAL INFORMATION | |
|--------------------------------|-------------------------|
| Dimensions | 2.03 x 2.03 x 0.85 m |
| Jets | 52 |
| Shell | White |
| Panels | EcoWood Grey |
| Weight without water | 400 Kg |
| Weight with water | 1500 Kg |
| Volume | 3.5 m ³ |
| EQUIPMENT SPECIFICATIONS | |
| Seats | 5 (2 lounged) |
| Filter | 1 (5.5 m ²) |
| Pump 1: Filtration and Massage | 1 – 370 / 1500 w |
| Pump 2: Massage | 1500 w |
| Ozone Equipment | 1 |
| Control System with Heater | 1 – 3000 w |
| RGB Leds | Perimeter |
| Cover | 1 |
| WATER CIRCUIT SPECIFICATIONS | |
| Water Capacity | 1100 |
| Drain Valve | 1 |
| ELECTRICAL SPECIFICATIONS | |
| Voltage | 220 - 240 V ~ |
| Max Absorbed Power | 3370 w |
| Frequency | 50 Hz |
| Amperage | 16 A |
| | |

Note : the standard measures may vary ±2cm



IMPORTANT: Important: The equipment must be connected to an exclusive and permanent power line capable to support installed power. Lighting and electrical receptacles must be located at least 1.5 meters from the equipment.

The circuit ground wire must be provided to take advantage of the designed-in safety features of the equipment.

The electric installation must be in accordance with actual legislation.